


(1) UNPUNCHED STUD,  
CAPPED w/(2) TRACKS.  
MEMBER SIZES AS REQ'D  
PER DESIGN.

(1)#10-16 SCREW  
TYP. EACH FLANGE

RedHeader PRO™ JAMB STUDS.  
MEMBER SIZE AS REQ'D  
PER DESIGN.



ATTACH EACH TRACK  
TO STUD USING:  
(2)#10-16 SCREWS  
@ 16"o.c.

CRIPPLE STUDS

(2)Bailey Universal Bridging Clip (UBC)  
Fy=50ksi  
TOP & BOTTOM  
1/2" LESS THAN STUD WIDTH.  
USE: (3)#10-16 SCREWS ON  
EACH LEG AS SHOWN ABOVE.  
USE PRE-PUNCHED HOLES  
FOR SCREW ATTACHMENT.

**BAILEY**®  
METAL PRODUCTS LIMITED

## LAY-IN SILL CONNECTION

LAY-IN SILL ATTACHED USING Bailey UBC

This detail library is intended to provide general framing details only and does not replace the judgments and designs of a qualified architect and/or engineer. The details are provided as a starting tool to assist the user in creating and detailing cold-formed steel framing construction details.  
Each detail including accompanying text must be thoroughly evaluated and approved by a qualified architect or engineer.

© Copyright 2017 ClarkDietrich Building Systems For more information visit [www.bmp-group.com](http://www.bmp-group.com) or call (905) 738-9267